

D2012S

High Speed Mini Centrifuge

Features

- Pulse operation for fast and convenient quick spins;
- Speed up to 15000rpm (15100xg) ;
- Brushless DC motor drive quickly to the target speed;
- Smooth and quiet operation (noise \leq 65dB) ;
- Automatic door lock and over-speed detection;
- Wide voltage technology:
speed is not affected by voltage fluctuations, high speed accuracy;



Applications

Microcentrifuges are mainly used in molecular biology laboratories for plasmid extraction; Nucleic acid purification; Pre-sequencing processing and other applications including extracting of DNA/RNA samples, sedimentation biological components, biochemical and chemical analyses of microsamples.



Specifications	D2012S
Max.Speed	15000rpm (300-15000rpm), increment:100rpm
Max.RCF	15100xg
Speed Accuracy	\pm 20rpm
Rotor Capacity	12 \times 0.2/0.5/1.5/2mL 18 \times 0.2/0.5/1.5/2mL 6 \times 0.5mL+6 \times 5mL 4 \times 0.2mL PCR 8-tube strip
Run Time	30s-99min
Driving Motor	Brushless DC motor
Safety Devices	Door interlock, over-speed detection, over-temperature detection, automatic internal diagnosis
Display	LCD
Power	100-240 V, 50/60 Hz; 70W
Noise Level	\leq 65dB
Dimension (D x W x H)	272mm \times 260mm \times 154mm
Weight	6.2Kg
Other functions	Speed/RCF switch, short-time run function, sound-alert function

A18-2P

Cat.No 19400158

Use for:D2012S
Max speed:15000rpm
Max RCF:16750 \times g
Rotor capacity:18 \times 0.2/0.5/1.5/2mL
Rotor material:High strength nylon
available rotor adapters:A02P2, A05P2



A6-5VP

Cat.No 19400156

Use for:D2012S
Max speed:15000rpm
Max RCF:16520 \times g
Rotor capacity:6 \times 0.5mL+6 \times 5mL
Rotor material:High strength nylon



A4-PCR8

Cat.No 19400157

Use for:D2012S
Max speed:15000rpm
Rotor capacity:4 \times 0.2mL
PCR 8-tube strip
Rotor material:zircal

